City of Beaumont Tow Truck Equipment / Documentation Checklist

Con	npany Name
Pern	nit Number Company Truck Number
Year	Make Model
VIN	
	Texas Tow Truck Registration Documents TDLR 86.200
	_ License Plate Number Expires
	_ Insurance Documents
	_ Cab Card
	_ Tx. Insp. Sticker Number Expires
	Tow truck of at least 3/4 ton in size
	Company Markings confirming to TDLR Rules 86.701
	_ TDLR IM markings
	Tow Truck equipped with Sling Wheel Lift Rollback
	Mechanical Winch or of the equipment sufficient to prevent swinging of vehicle being towed. Must have one of the following: (1) A legible manufacturer's data plate indicating the capacity of the boom, the winch or the carry mechanism; or (2) A document in the truck from the manufacturer stating the capacity of the boom, the winch or the carry mechanism. The winch must not exceed the capacity of the boom or leak oil.
	Every Hydraulic line must be free of leaks and be in gook working condition, free of defects
	D 4 02

The cables must be as specified by the manufacturer and be in good condition, with in Manufacturer's guidelines					
J hook up chains and at least two 5/16 inch link steel safety chains for tow trucks with a registered weight of 10,000 lbs. Or two 3/8 inch link safety chains or their equivalent fo tow trucks over 10,000 lbs.					
Straps and tie downs as specified by manufacturer.					
Tow dollies as needed					
One 10 lb or two 5 lb multiple purpose fire extinguisher, in good condition.					
Gloves					
Wheel chocks					
36 inch crow or pry bar					
5 gallon trash receptacle					
18 inch broom head and a flat edge shovel					
Spot light or flashlight					
Triangles reflectors, flares, cones, safety lights or other appropriate safety signals					
Outside rear view mirrors on both sides of the truck					
Magnetic tow lights unless wireless, with appropriate cable or cushions to protect vehicle					
Tow truck must have working; Headlights Hazard lights Tail lights					
Brake lights Emergency lights Windshield wipers					
Tires in good condition					
Brakes sufficient for controlling truck and towed vehicles					

Note: Trucks with a slip in bed must have the bed secured to the frame of the truck by a minimum of eight $\frac{1}{2}$ " diameter bolts with at least 4 at the front of the slip bed.

Driver requirements

	_ Display appropriate	TDLR issued original towing operator license.
	policy. TDL	s a condition of their license must comply with the protective clothing R 86.1000 (b) y marked with the tow company's name
meet	for high	or reflective jacket that meets the ANSI/ISEA 207-2006 requirements visibility safety apparel, or, during daylight hours, a flourescent shirt the same safety requirements.
	This vehicle was in	spected and a road test was witnessed on the day of
20	by	of the Beaumont Police Department. As a result of
the	inspection and road tes	st the vehicle was found to:
	Q	ualify
	No	ot Qualify
	registration and i City of Beaumor	ssuance of a permit to be operated as a tow truck in it.
——— Printe	d name of inspector	Signature of inspector